Fujitsu recommends Windows® 7.



Data Sheet Fujitsu ESPRIMO Q900 Desktop PC

The Mini with More PC per cm³

The Fujitsu ESPRIMO Q900 delivers excellent performance, energy efficiency and manageability in a mini PC. An Intel® Core™ i3 or i5 processor and Intel® vPro™ technology deliver professional computing and management. Its stylish design is also practical, with two front USB 3.0 ports for lightning fast connections.

An elegant PC for challenging tasks

Eye-catcher on every desk with a modern and exclusive design

■ Fully equipped mini PC with a volume of 1.6 liters weighing 1.4 kg

A black shell and a green core

The most energy-efficient computer of our Fujitsu ESPRIMO series reduces your energy consumption

■ Intel® Mobile Technology for 13-watt power consumption in idle mode, extended power management settings and an up to 90% energy efficient AC adapter

Small, flexible and powerful

Intelligent performance using the latest Intel technology and high flexibility to meet all requirements

■ 2nd generation Intel® Core™ i5 processor, genuine Windows® 7 Professional, up to 8 GB memory, 500 GB hard disk drive, 5 USB 2.0 ports, 2 USB 3.0 ports, a display port and multi-card reader

System management

Simple system administration for complex IT infrastructures

■ Intel® vPro™ technology (depending on CPU) and DeskView manageability

Quiet

Pleasant working environment due to an extremely quiet system

■ New fan concept for even lower noise levels

























Page 1 / 7 http://ts.fujitsu.com/ESPRIMO

Components

Processor	Intel® Core™ i5-2520M processor (2 Cores / 4 Threads, 2.5 GHz, 3 MB, Intel® HD Graphics 3000)
	Intel® Core™ i3-2330M processor (2 Cores / 4 Threads, 2.20 GHz, 3 MB, Intel® HD Graphics 3000) *
	Intel® Pentium® processor B940 (2 Cores / 2 Threads, 2.00 GHz, 2 MB, Intel® HD Graphics) **
	Intel® Celeron® processor B800 (2 Cores / 2 Threads, 1.50 GHz, 2 MB, Intel® HD Graphics)
	*Processor only for SMB, education and government
	**Processor only for SMB
	Intel® vPro™ Logo with Intel® Core i5-2520M processor.
Operating systems	
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit
	Genuine Windows® 7 Home Premium 64-bit
	Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	Genuine Windows Vista®
operating system compatible	Genuine Windows vista Genuine Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via
operating system notes	http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1333 MHz, PC3-10600, SO DIMM
	4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1333 MHz, PC3-10600, SO DIMM
Hard disk drives (internal)	
Haid disk drives (internal)	SSD SATA, 128 GB, 2.5-inch, full disk encryption
	SSD SATA, 128 GB, 2.5-inch
	SATA, 5400 rpm, 250 GB, 2.5-inch
	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
	HDD SATA II, 5400 rpm, 500 GB, 2.5-inch*
land dialement	HDD SATA II, 5400 rpm, 320 GB, 2.5-inch*
Hard disk notes	*Disk imaging software of the customer must be 4k sector size / advanced format ready Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	DP to DVI-D (single link) Adapter Cable
Drives (optional)	Blu-ray Combo SATA Slot-in slim
	Card Reader 8-in-1 ESPRIMO Q
	DVD Super Multi Slot-in slim
Interface add on cards/components (optional)	
	WLAN 2x2 agn
	Bluetooth Q900
Base unit	ESPRIMO Q900
Mainboard	
Formfactor	proprietary
Chipset	Intel® QM67
Processor socket	rPGA 989A/B
Processor quantity maximum	1
Memory slots	2 SO DIMM (DDR3, 1333 MHz)
Mamary fraguancy	1333 MHz
memory frequency	
Memory frequency Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity
	per channel has to be the same

Page 2 / 7 http://ts.fujitsu.com/ESPRIMO

Mainboard	
Integrated WLAN	1 (optional)
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software
	Recovery BIOS
Audio and an	Unified Extensible Firmware Interface (UEFI)
Audio codec Audio features	Realtek ALC662 Support of high-definition audio for S/PDIF output with up to 5.1 channels
	Support of high-definition addition of step in output with up to 5.1 channels
I/O controller on board	
Serial ATA total	1
Controller functions	Serial ATA II (3 Gbit)
	NCQ
	AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out / headphones / SPDIF	1 (optical)
USB 2.0 total	5
USB 3.0 total	2
USB front	2
USB rear	5
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Ethernet (RJ-45)	1
Kensington Lock support	1
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB tilt wheel mouse
Drive bays	
Drive bays total	2
2.5-inch bays	1
5.25-inch external bays	1
Drive bay notes	slim slot-in
Graphics on board	
Graphics brand name	Intel® HD Graphics or HD Graphics 3000 (depending on CPU)
Shared video memory	up to 1759 MB
Refresh rate 1024 x 768 (recommended / max.)	
Refresh rate 1280 x 1024	-/-
(recommended / max.)	
Refresh rate 1600 x 1200	-/-
(recommended / max.)	
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel 1680 x 1050 pixel
	1920 x 1030 pixel
	1920 x 1200 pixel
	·

Page 3 / 7 http://ts.fujitsu.com/ESPRIMO

Craphics on heard	
Graphics on board	1200 700 + 1
TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel 1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1030 pixel
	1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel
Tri lesolution (DisplayFort)	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
	2560 x 1440 pixel
	2560 x 1600 pixel
Graphics features	DirectX® 10.1 support
p	HDCP support
	Dual display support
	OpenGL® 2.1
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
Operating voltage range	100 V - 240 V (AC Input)
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	external (90W)
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=ca024c84-ccbf-459f-b9eb-b5fb049daa11
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD, (ODD)
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core i5-2540M
Noise Operation mode 1: ODD load	4.6 B / 32 dB(A)
(Blue angel requirement) Noise Operation mode 2: HDD load	3.3 B / 18 dB(A)
(Blue angel requirement)	אן אט או די די (A) איז און איז
Noise Operation mode 3: CPU 90% load	4.1 B / 27 dB(A)
(Blue angel requirement)	ינט <i>ו בו</i> עט (A)
Noise Operation mode 4: High load	4.1 B / 27 dB(A)
Noise Operation mode 5: Office	3.3 B / 18 dB(A)
applications	אן אין איז
Idle mode (Blue Angel requirement)	3.3 B / 19.0 dB(A)
Noise notes / description	Noise for standard configuration CPU, HDD, ODD; A weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)), (bystander position) (ISO9296)
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	165 x 168 x 57 mm
Operating position	Backpack solution (optional)
Weight	approx. 1.4 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	5 - 35°C
-	

Page 4 / 7 http://ts.fujitsu.com/ESPRIMO

Compliance	
Compliance Product	ESPRIMO Q900
Model	MPC-D1009
	(F
Europe	Nordic Swan
Global	RoHS (Restriction of hazardous substances)
diodai	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	ENERGY STAR®
	EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Additional Software	
Additional software (preinstalled)	Nero Essentials S (burning software)
,	Fujitsu Recovery (Hard Disk Based Recovery)
	Norton Internet Security (incl. Firewall) 60 days version
	Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy
	Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	Nero 9 Essentials XL
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not
	supported under Windows XP if the system runs on Intel onboard graphics)
Manageability	
Manageability technology	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	iAMT 7.0
	DeskUpdate Driver management
Manageability software	DeskView 10.x client management including:
David Million and a same	DASH 1.1 remote system management
DeskView components	On/Offline remote client management Detailed system inventory management and reports
	BIOS Management
	Remote power management
	System notifications
	Security Remote Control
	DeskView Helpdesk Integration
	WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability
	http://www.altiris.com/fujitsu
	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
Security	
System protection	Kensington Lock support
Audit proof protection	Write protect option for the Flash EPROM
	Embedded security (TPM 1.2)
	Control of all USB interfaces External USB ports can be disabled congrately
	External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password
	Hard disk password
	Optional: Access protection via external SmartCard reader
Packaging information	
Packaging dimension	395x198x284 mm
Max. quantity / pallet	48
Material - Weight (g) Carton	670g
Material - Weight (g) EPS / PS	appr. 10 g
	~rr · · · · · · · · · · · · · · · · ·

Page 5 / 7 http://ts.fujitsu.com/ESPRIMO

Packaging information	
Material - Weight (g) PE	аррг. 125 g
Packaging notes	printed user documentation is bleached in chlorin free process
Warranty	
Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Service	es - the perfect extension
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice



Page 6 / 7 http://ts.fujitsu.com/ESPRIMO

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO Q900, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO Q900, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2011-12-20 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions